



www.wearwell.com

ErgoDeck MAX Diamond-Plate

Group 599



Gone are the days of having to choose between comfort and customization. Introducing a modular tile that takes flexibility, performance, and safety to the max - ErgoDeck MAX. ErgoDeck Max with [LockSafe](#) technology holds secure but can be taken apart and reconnected on demand. This revolutionary product utilizes a universal edging system for simple configuration and installation. Each section features counter-sunk holes for semi-permanent installations and traction bars for added [slip prevention](#). ErgoDeck Max carries a Limited-Lifetime Warranty.

10% cost savings over customized matting.

Save saves hundreds, if not thousands of dollars on mat replacement, labor, and downtime by replacing tiles, not an entire mat.

- U.S. PATENT NO. 10,914,081; 11,174,648; D502,557; D520,650
- Comfortable sponge base
- NFSI Certified
- Modular to fit any space
- Easy to install, universal ramps
- 100% Silicone Free
- Overall thickness 7/8" (22 mm)

Learn more about ErgoDeck MAX [here](#).

Type	Anti-Fatigue Flooring
Suitable Environment	Dry
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	PVC/Nitrile Sponge
Recycled	<30%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .65
Compression Deflection	ASTM D575-91 / 14.15%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
599.78x18x18BK-CS10	715411698424	Black	0.875	18" x 18"	Y	CS-10
599.78x18x18CH-CS10	715411698431	Charcoal	0.875	18" x 18"	Y	CS-10

